



THE SOUND OF SUPERIOR QUALITY

8, Derwent Business Centre, Clarke Street, Derby DE1 2BU, UK. Tel +44 (0)1332 342233. Fax +44 (0)1332 342373  
[www.blackrhodium.co.uk](http://www.blackrhodium.co.uk) [info@blackrhodium.co.uk](mailto:info@blackrhodium.co.uk)

**Black Rhodium Introduces a new Pure Silver Interconnect with Vibration Stabiliser**

## **ORATORIO DCT++CS**



Oratorio DCT++CS with GN-4R DCT++ and Crystal Sound Treated Rhodium Plated RCA connectors



Oratorio DCT++CS with DCT++ and Crystal Sound Treated Rhodium Plated XLR connectors

***Digital Versions Also Available***

Black Rhodium announces the launch of the new ORATORIO stereo interconnect cable.

**ORATORIO DCT++ CS** is made from 99.99% pure silver wire. Silver wire has been chosen for **ORATORIO DCT++ CS** because silver wire delivers superior sound quality to all other less expensive metals and is highly conductive.

***Advanced Cryogenic and Crystal Sound Processing for a Superior, High Impact Sound.***

**ORATORIO DCT++ CS** is treated with our advanced DCT++ Deep Cryogenic Treatment. This involves temperature processing above and below room temperature. The DCT++ process alters the molecular structure of the cable to improve uniformity. The benefits of this are everlasting and bring an improvement to every single aspect of the cables performance.

In addition to DCT++ **ORATORIO DCT++ CS** is also treated with the Crystal Sound Process. The Crystal Sound process, which is applied to the cable following the completed DCT++ process, refocuses the outermost skin of the conductor. The result is that the surface of the conductor is more closely packed and regular, and has a continuity which aids conduction through removal of voids left by the drawing process.

The main benefits of the Crystal Sound process are that bass notes sound more powerful and refined (you will notice a smaller cable can give the same performance as a much larger cable) and other notes will have greater clarity in their sound.

***Low Loss PTFE Insulation used to Reduce Time Smeared Distortion.***

The silver wires in **ORATORIO DCT++CS** are insulated in PTFE because its low dielectric loss ensures extremely low distortion due to dielectric absorption effects in which sound energy is absorbed in the insulation and released at a later interval of time to create highly

audible time-smearing distortion. Dielectric distortion is further reduced by a layer of air separating the wire from the inner wall of the insulation along its length.

### ***Vibration Stabiliser Cuts Audible Distortion from Mechanical Vibration***

**ORATORIO DCT++ CS** is fitted with two GRAHAM NALTY LEGACY RANGE VS-2 Vibration Stabilisers. The Vibration Stabiliser has been specially designed to reduce audible cable distortion in cables by limiting the effects of vibrations travelling through the conductor wires which can cause audible distortion to your music. Mechanical vibration within audio cables changes the electrical characteristics of the cable seen by the sensitive electrical voltages that carry the music signal. The effect of these changes in electrical characteristics is to modulate the sound signal and create the intermodulation effects that we hear as noise and distortion in the music. By applying Vibration Stabilisers at both ends of the cable, mechanical vibration introduced at either end of the cable is very effectively reduced.

The benefits of a tighter sound of the VS-2 are enjoyed in all types of music, but in particular plucked strings such as double basses and harps are reproduced in a much sharper presentation, and massed voices in a choir sound more like a choir of individual voices.

### ***Anti RFI / EMI Technology to Reduce Distortion.***

**ORATORIO DCT++CS** is covered in a braided screen to protect the inner cores from picking up radio frequency interference (RFI) by twisting the cores. The screen is connected at only end only to prevent 'loop aerials' between equipment picking up noise. An untwisted cable has a large surface area that can more easily pick up RFI/EMI signals generated from Radio, Wifi, Mobile Phones and even central heating systems.

Complementary filtering techniques are additionally applied to ensure that any interference that does penetrate the cable's very effective defences is effectively neutralised preventing audible distortion interfering with the music.

All these treatments are designed to reduce the amount of audible distortion in the cable, allowing cleaner, clearer sounds to be enjoyed from your equipment.

### ***Advanced Manufacturing Techniques to Reduce Noise.***

**ORATORIO DCT++CS** uses two separate cores for positive and negative signal flows. These are connected in opposite directions from the way they were wound on the reel. Our listening tests have shown when connected this way the noise floor between the musical notes lowers. This gives 'blacker' silences in the interval between musical notes and enhances reproduction of the musical edges and natural decays in music.

### ***High End Rhodium Cryogenically Processed Rhodium Plated Connectors***

**ORATORIO DCT++CS** is terminated with ultra-high quality Rhodium Plated plugs. The RCA version is terminated with specially designed GRAHAM NALTY LEGACY RANGE GN-4

RCA connectors. These have been specially manufactured to ensure that Black Rhodium cables deliver the very best sound quality possible. The XLR connectors are the new Black Rhodium XLR connectors designed especially for use in Black Rhodium cables.

Rhodium plating is applied to the plugs to ensure a cleaner and less corroded contact is maintained between the plug and socket. The benefit of rhodium plating over gold plating is a much livelier and more exciting sound from the music.

The sound quality is further improved by applying the same DCT++CS process to the connectors that is used for the wire on the connectors.

Specification of Black Rhodium **ORATORIO DCT++CS** stereo interconnect cable

- 99.99% pure silver conductor wires
- Cryogenically treated conductors with additional Crystal Sound technology
- Insulated in PTFE for low dielectric absorption and clearer sound
- Braided silver plated copper screen to reduce RFI noise and distortion
- All connectors rhodium plated for long term reliability and resistance to corrosion
- All connectors cryogenically treated with additional Crystal Sound technology
- Attractive deep purple outer braid
- Cables can be supplied with either RCA or XLR connectors
- Capacitance of RCA terminated 1m cable 75pF
- Capacitance of XLR terminated 1m cable (Positive to Negative) 60 pF
- Vibration Stabiliser weights 2 x 85 g